



**PRODUCT FACT SHEET**

**STREAMLIGHT 3C Luxeon DIVISION 1/DIVISION 2 PROPOLYMER®**  
**ALKALINE BATTERY-POWERED FLASHLIGHT**

**MARKET APPLICATIONS:** Industrial, Occupational Safety, Fire & Rescue, Sporting Goods, Hardware/Tool, Consumer

**DESCRIPTION:** The 3C Luxeon ProPolymer is a high performance, 3C alkaline powered, Super High Flux Luxeon LED flashlight. This light features a body constructed of a Polymer Engineering resin that is virtually indestructible, shock resistant, non-conductive and light weight. The light case is "O" ring sealed and water proof.

**CASE MATERIAL:** Impact resistant Engineering Polymer resin. Available in black or high visibility yellow. The lens cover is made from the same impact resistant polymer as the body.

**DIMENSIONS:** Length: 9.30 in. (23.62 cm) Diameter: Major Diameter: 2.0 in. (5.08 cm)  
Body Diameter: 1.48 in. (3.76 cm)

**WEIGHT:** 7.3 ounces (207 grams) 14.6 ounces (414 grams)\*

**LENS:** Unbreakable polycarbonate lens with scratch resistant coating.

**LIGHT SOURCE:** One (1 Watt) Super High Flux Luxeon LED, 10,000 hour LED life

**LIGHT OUTPUT:** LED Rating: 44 Lumens typical  
Up to 3,500 Peak Beam Candlepower

**ON/OFF:** Rubber booting, tail-end, push button switch for one-handed operation.

**RUN TIME:** DIVISION 1: 4 hours continuous at full intensity. Up to 15 hours to 50% output intensity.  
Up to 24 hours to 25% output intensity.  
DIVISION 2: 5.5 hours continuous at full intensity. 2 additional hours of declining output.

**BATTERY:** Three (3) "C" size alkaline batteries.

**FEATURES:** IP67 Ingress Protection  
1 Watt Super High Flux Luxeon Star  
Non-conductive  
Shock resistant (Drop Test verified)  
Corrosion proof  
Deep Parabolic Beam Generator produces long range brilliance and smooth uniform pattern.  
Solid State Power Regulation provides maximum light output throughout battery life.

**APPROVALS\*\*:** Most models meet applicable European Community Directives.   
DIVISION 1: UL Classified Class I, Division 1, Groups C & D;   
Class II, Division 1, Groups F & G; Class III; Exia  Temperature Code T4  
DIVISION 2: UL Listed Class I, Division 2, Groups A, B, C & D;   
Class II, Division 2, Groups F & G; Class III; Temperature Code T5

**WARRANTY:** Limited lifetime warranty.

**OPTIONAL ACCESSORIES:** Holster, Traffic Wand

\*With batteries \*\* See product for specific ratings.

**Assembled In The USA.**