PRODUCT FACT SHEET

SL-20XP® LED

LIGHTWEIGHT RECHARGEABLE FLASHLIGHT

MARKET APPLICATIONS: Law Enforcement, Fire & Rescue, Utility, Security, Automotive, Industrial, Sporting Goods, Consumer

DESCRIPTION: The SL-20XP® LED is a full size professional grade, lightweight, high-intensity, rechargeable flashlight with LED back up illumination.

CASE MATERIAL: Lightweight, super-tough nylon polymer case designed with non-slip rubber comfort grip. Available in high visibility yellow, safety orange or non-glare black.

DIMENSIONS: Length: 13.2 in. (33.5 cm) Diameter: Major Diameter: 2.50 in. (6.35 cm)
Body Diameter: 1.50 in. (3.81 cm)

WEIGHT: 1.1 lb. (.50 kg) with battery

LENS: Unbreakable polycarbonate lens with scratch-resistant coating. O-ring sealed.

LIGHT SOURCE: 8-watt, 6-volt halogen bulb with 100 hour lifetime.
3 High Intensity White LEDs with 100,000 hour lifetime.

LIGHT OUTPUT: See chart.



ON/OFF: Dual switch control for halogen and LEDs.
Halogen: Momentary and constant on.
LEDs: Constant on.

RUN TIME: See chart.
All claims to 10% of initial lumen output level.

BATTERY: 5-cell, 6.0 Volt Nickel-cadmium sub-C battery, rechargeable up to 1000 times.

CHARGING: 10 hour overnight charger-holder, available with 100V, 120V, 230V, 240V AC or 12V DC charge cords.

FEATURES: IPX4 rated design; water resistant operation.
1 meter impact resistance tested.
Serialized for positive identification.

WARRANTY: Streamlight warrants this product to be free of defect for a lifetime of use. We will repair, replace or refund the purchase price, at our option, of any Streamlight product that does not work or that you manage to break for as long as you own it. Of course, this limited lifetime warranty excludes abuse, batteries, bulbs and chargers. Rechargeable batteries and chargers have a one (1) year warranty with proof of purchase.

APPROVALS: Meets applicable European Community directives. CE

OPTIONAL ACCESSORIES: Safety wands, 5-Unit Back Charger, Ring holder and Holster.

	FL1 STANDARD	HALOGEN	3 LEDs
OUTPUT		120 LUMENS	20 LUMENS
RUNTIME		1h 30min	11h 30min
DISTANCE		253m	28m
INTENSITY		16,000cd	200cd



All performance claims tested to ANSI/NEMA FL1-2009 Standard

Issued: 10/01/04

Revised: 05/06/10 **Rev:** 3

Assembled In The USA.

Document #142