

# KNUCKLEHEAD® HAZ-LO® SPOT LED WORKLIGHT

FL 1 STANDARD	HIGH	LOW
	<b>150</b> LUMENS	<b>55</b> LUMENS
	<b>3h 30min</b>	<b>12h</b>
	<b>227m</b>	<b>131m</b>
	<b>12,900 cd</b>	<b>4,300cd</b>



Head rotates 360°  
Articulates 210°



Stowable hook  
to hang for  
hands-free use

Sturdy clip attaches  
to turn out gear,  
belts and harnesses

Removeable, powerful magnet includes  
a cover to protect painted surfaces

- Material/Lens** Housing, base and battery housing made from high impact super tough nylon offering exceptional durability. All openings are O-ring sealed for weather resistance. Circular rare-earth magnet surrounded by durable nickel plated steel housing. One way valve for case venting; Unbreakable polycarbonate with silicone anti-scratch coating assembled in a heavy duty bezel. O-ring sealed.
- Dims/Weight** Height: 9.20 in. (23.4 cm) Width: 2.85 in. (7.2 cm) Thickness (at magnet): 2.75 in. (7.0 cm) NiCd: 23.1 oz (655 grams) Alkaline: 18.3 oz (519 grams)
- Light Source** One C4® LED, impervious to shock with a 50,000 hour lifetime..Single parabolic reflector provides a tighter beam for longer range target illumination. 4 lighting modes:  
 - High for a tight, far-reaching beam: 150 lumens; 12,900 candela; 227m beam distance; runs 3.5 hours  
 - Low for when less light is ideal and for longer run times; 55 lumens; 4,300 candela; 131m beam; runs 12 hours  
 - Moonlight for low-level lighting and extended run times - runs 20 days  
 - Flash for signaling - runs 8 hours  
 Optimized electronics provide regulated intensity
- Switch** Sonic welded push button switch designed for extremely long life. Rubber dome push button actuator provides easy operation even when wearing heavy gloves.
- Battery** Industrial rechargeable nickel-cadmium 4.8 volt, 1.8 amp hour, 4 cell sub-C can be recharged up to 1,000 times. Optional four "AA" alkaline non-rechargeable battery pack provides fast replacement with readily available batteries.
- Charging** AC and DC one-hour fast chargers with full charge indicators designed specifically for AC or DC power sources. The universal Steady Charger, which requires up to 10 hours for a complete charge using AC or 12V DC charge cord. Optional PiggyBack® charger allows for simaltenously charging of the Knucklehead and a spare battery so you always have a light when you need it.
- Features** Full 360 degree rotation head with 210 degrees of articulation  
 IPX4 water-resistant All openings o-ring sealed  
 2 meter impact resistance tested  
 Removable magnet with 135 lb pull strength  
 Serialized for positive identification
- Approvals** Class I & II Division 1, Groups C,D,F,G; Class III; T-Code: T4; Exia;  
 NON-INCENDIVE: Class I Division 2; Groups A,B,C,D, T-CODE T4  
 Permissible Flashlight; Approval. No. 20-4140001-0: Tested for Intrinsic Safety in Methane-Air mixtures only. Charge or replace batteries in fresh air only  
 Charger meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position  
 Meets applicable European Community Directives.
- Warranty** Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.

Item Description	UPC	Part #
Knucklehead HAZ-LO Spot IEC Type C (230V) AC/12V DC - Yellow	080926-91728-6	91728
Knucklehead HAZ-LO Spot IEC Type C (230V) AC/12V DC - Orange	080926-91758-3	91758
Knucklehead HAZ-LO Spot 240V AC/12V DC - Yellow	080926-91729-3	91729
Knucklehead HAZ-LO Spot 240V AC/12V DC - Orange	080926-91759-0	91759
Knucklehead HAZ-LO Spot 120V AC/12V DC - Yellow	080926-91727-9	91727
Knucklehead HAZ-LO Spot 120V AC/12V DC - Orange	080926-91757-6	91757
Knucklehead HAZ-LO Spot IEC Type A (100V AC)/12V DC - Yellow	080926-91730-9	91730
Knucklehead HAZ-LO Spot IEC Type A (100V AC)/12V DC - Orange	080926-91760-6	91760

Item Description	UPC	Part #
Knucklehead HAZ-LO Spot 120V AC - Yellow	080926-91722-4	91722
Knucklehead HAZ-LO Spot 120V AC - Orange	080926-91752-1	91752
Knucklehead HAZ-LO Spot without charger - Yellow	080926-91721-7	91721
Knucklehead HAZ-LO Spot without charger - Orange	080926-91751-4	91751
Knucklehead HAZ-LO Spot - Alkaline Yellow - Blister	080926-91742-2	91742
Knucklehead HAZ-LO Spot - Alkaline Orange - Blister	080926-91744-6	91744

Assembled in USA



Item	UPC	Part #
DC2 direct wire charge cord	080926-22050-8	22050
DC1 Charge Cord	080926-22051-5	22051
120V AC charge cord	080926-22311-0	22311
240V AC charge cord*	080926-22241-0	22241
IEC Type C (230V) AC charge cord	080926-22061-4	22061
IEC Type A (100V/120V) AC charge cord	080926-22060-7	22060
Steady Charge (SC) Plug-In Charger Holder**	080926-90010-3	90010
AC Fast Charger/Holder	080926-90011-0	90011
DC #1 Fast Charger/Holder	080926-90012-7	90012
DC #2 Fast Charger/Holder	080926-90013-4	90013
Steady Charge (SC) PiggyBack® Charger	080926-90110-0	90110
AC PiggyBack® Fast Charger	080926-90111-7	90111
DC #1 PiggyBack® Fast Charger	080926-90112-4	90112
DC #2 PiggyBack® Fast Charger	080926-90113-1	90113
NiCd Battery Pack (Orange Sleeve)	080926-90335-7	90335
Bank Charger (SC) 120V AC	080926-90400-2	90400
Bank Charger 12V DC	080926-90401-9	90401
Alkaline battery carrier (Batteries not included)	080926-90542-9	90542

\*Not shown  
\*\*Cords not included

