



TLR-1® HP/ TLR-1®s HP/ TLR-1® GAME SPOTTER™
LONG RANGE RAIL MOUNTED TACTICAL LIGHT

MARKET

APPLICATIONS: Law Enforcement, Security, Military, Home Defense, Sporting Goods

DESCRIPTION: Long range, lithium battery powered Gun-Mounted Tactical Light featuring the latest in shock-proof power C4®LED technology and providing 1.75 hours of continuous regulated run time. The TLR-1® GAME SPOTTER™ features a shock-proof green power LED. Rail clamp designed to rapidly attach/detach from side of weapon. Models available with either standard door switch or remote door switch. All models offer a tethered battery door and latch mechanism that prevents battery door loss while providing easy battery replacement. When enabled, strobe activated on two or more momentary paddle hits (TLR-1®s HP only).

CASE MATERIAL: 6000 Series machined aircraft aluminum with black anodized finish.

DIMENSIONS: Length w/standard switch: 4.83 in. (12.27 cm) Length w/remote switch: 5.25 in (13.34 cm)
Body Width: 1.44 in. (3.66 cm) Head Diameter: 2.20 in (5.59 cm)

WEIGHT: 5.3 oz (150.3 grams) with standard switch and batteries (included in purchase).
5.6 oz (158.8 grams) with remote switch and batteries (included in purchase).

LENS: Unbreakable polycarbonate lens with scratch-resistant coating. O-ring sealed.

LIGHT SOURCE: TLR-1® HP/TLR-1s® HP: C4®LED, white, impervious to shock with a 50,000 hour lifetime.
TLR-1® GAME SPOTTER™: C4®LED, green (520-535nm), impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: TLR-1® HP/TLR-1s® HP: 46,000 candela peak beam intensity and 200 lumens measured system output.
TLR-1® GAME SPOTTER™: 31,000 candela peak beam intensity and 150 lumens measured system output. Deep-dish parabolic reflector produces a long range targeting beam with optimum peripheral illumination.

ON/OFF: Standard Switch: Ambidextrous momentary/steady On-Off.
Remote Switch: Momentary/steady On-Off and port plug for remote switch assembly.
Double tap of momentary paddle within 0.4 seconds activates strobe. (TLR-1®s HP only)
Strobe can be disabled. (TLR-1®s HP only)

RUN TIME: 1.75 hours regulated run time. Solid-state current regulation for consistent illumination level.

BATTERY: Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.

FEATURES: C4®LED technology
Ambidextrous momentary/steady On-Off switch (standard switch only).
One handed snap-on/tighten interface keeps hands away from muzzle when attaching/detaching.
Securely fits a broad range of weapons.
Mounts directly to all MIL-STD-1913 (Picatinny) rails and weapons with Glock-style rails.
Includes keys for Glock-style, Picatinny, Beretta 90two, S&W 99 and S&W TSW.
Extensively live-fire tested impact resistant construction.
Operating temperature: -40°F to +120°F.
IPX7 rated design; waterproof to 1 meter for 30 minutes.
Strobe can be disabled. (TLR-1®s HP only)

APPROVALS: Meets applicable European Community Directives. **CE**

WARRANTY: Streamlight's Limited Lifetime Warranty.

OPTIONAL ACCESSORIES: Mounting Adapters, Remote Switches

NOTE: NIGHT HUNTING WITH ARTIFICIAL LIGHT MAY BE PROHIBITED OR RESTRICTED IN YOUR STATE. PLEASE CHECK YOUR STATE'S GAME LAWS FOR CLARIFICATION.